

QC STL PRO-5.5X Specifications

| | | |
|--|---|--|
| Motor Voltage | 120 VAC, 60 Hz | |
| Energy Use | Hi: 490 Watts / Med: 268 Watts / Low: 88 Watts | |
| Air Flow | Hi: 5044 CFM / Med: 4238 CFM / Low: 2870 CFM | |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 3750 CFM / Med: 3070 CFM / Low: 2010 CFM | |
| dBA | Hi: 50.7 / Med: 45.7 / Low: 35.6 | |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 1681 SQFT to 2522 SQFT | |
| Minimum Attic Clearance | 38" | |
| # of Speeds | 3 | |
| Duct Diameter | 20" | |
| Duct Length | 9 feet | |
| Motor Head Diameter | 20 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls | Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit | |
| Warranty | 15 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 6.73 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 30 1/4" | |
| Removable Grille Outside Dimension | 16" x 32" | |
| Shipping Weight | 75 lbs. | |
| Box Dimensions | 39" x 24" x 39" | |
| In The Box | -QC STL PRO-5.5X Motorhead -Removable Grille -Cut-out Template -Window Locks | -Damper Box -9 Foot Duct -Accessory Bag -Controls |

